



























Table of Contents








	Seite
1. up cut router bits	
1.1. shaft diameter 3,0 mm	2
1.2. shaft diameter 4,0 mm	2
1.3. shaft diameter 6,0 mm	3
1.4. shaft diameter 8,0 mm	8
2. down cut router bits	
2.1. shaft diameter 3,0 mm	9
2.2. shaft diameter 6,0 mm	10
3. special shape router bits	
3.1. compression cut router bits	10
3.2. V-groove router bit	10
3.3. engraving bits	11
3.4. micro-toothed router bits	12
3.5. diamond polish tool	12
4. coated router bits	
4.1. XOX coating for aluminum and aluminum composite panels	13
4.2. DLC coating for plastics	14






Item	Technical data	Replacement for			
<i>* Balancing licensed from Datron AG</i>					
1.1. Up cut router bit, Shank diameter 3,0 mm					
CE-RB071 	Shank diameter	3,00 mm	Zünd (1)	R40	3910730
	Total length	38,00 mm	Zünd (2)	R71	3910752
	Number of flutes	1	Kongsberg (1)	BIT-MUS03-1004-38	42443390
	Cutting edge diameter	1,00 mm	Kongsberg (2)	BIT-AUS03-1004-30	42443614
	Max. cutting length	4,00 mm			
	Helix	up			
	Max. RPM	65.000			
		<i>balanced* and polished</i>			
CE-RB072 	Shank diameter	3,00 mm	Zünd (1)	R41	3910734
	Total length	38,00 mm	Zünd (2)	R72	3910753
	Number of flutes	1	Kongsberg (1)	BIT-MUS03-2006-38	42443416
	Cutting edge diameter	2,00 mm	Kongsberg (2)	BIT-AUS03-2006-30	42443630
	Max. cutting length	6,00 mm			
	Helix	up			
	Max. RPM	65.000			
		<i>balanced* and polished</i>			
CE-RB074 	Shank diameter	3,00 mm	Zünd (1)	R42	3910735
	Total length	38,00 mm	Zünd (2)	R74	3910755
	Number of flutes	1	Kongsberg (1)	BIT-MUS03-3006-38	42443432
	Cutting edge diameter	3,00 mm	Kongsberg (2)	BIT-AUS03-3006-30	42443689
	Max. cutting length	6,00 mm	Summa	500-9872	
	Helix	up			
	Max. RPM	65.000			
		<i>balanced* and polished</i>			
CE-RB075 	Shank diameter	3,00 mm	Zünd (1)	R43	3910737
	Total length	38,00 mm	Zünd (2)	R75	3910756
	Number of flutes	1	Kongsberg (1)	BIT-MUS03-3011-38	42443440
	Cutting edge diameter	3,00 mm	Kongsberg (2)	BIT-AUS03-3011-38	42443697
	Max. cutting length	11,00 mm	Summa	500-9850	
	Helix	up			
	Max. RPM	65.000			
		<i>balanced* and polished</i>			
1.2. Up cut router bit, Shank diameter 4,0 mm					
CE-RB050 	Shank diameter	4,00 mm	Zünd (1)	R50	3910718
	Total length	50,00 mm	Summa	500-9874	
	Number of flutes	1			
	Cutting edge diameter	4,00 mm			
	Max. cutting length	14,00 mm			
	Helix	up			
	Max. RPM	50.000			
		<i>balanced* and polished</i>			





Item	Technical data		Replacement for		
<i>* Balancing licensed from Datron AG</i>					
1.3. Up cut router bit, shank diameter 6,0 mm					
CE-RB112 	Shank diameter	6,00 mm	Zünd (1)	R102	3910742
	Total length	50,00 mm	Zünd (2)	R112	3910762
	Number of flutes	1	Kongsberg (1)	BIT-MUS06-2006-50	42437913
	Cutting edge diameter	2,00 mm	Kongsberg (2)	BIT-AUS06-2006-50	42437897
	Max. cutting length	6,00 mm	Summa	500-9875	
	Helix	up			
	Max. RPM	50.000			
	<i>balanced* and polished</i>				
CE-RB202  <small>Zentrierzahn / Centering tooth</small>	Shank diameter	6,00 mm	Zünd (1)	R202	5209418
	Total length	58,00 mm	Zünd (2)	R207	5212027
	Number of flutes	1			
	Cutting edge diameter	2,00 mm			
	Max. cutting length	6,00 mm			
	Helix	up			
	Max. RPM	50.000			
	<i>balanced* and polished</i>				
CE-RB2065  <small>Zentrierzahn / Centering tooth</small>	Shank diameter	6,00 mm			
	Total length	58,00 mm			
	Number of flutes	1			
	Cutting edge diameter	2,00 mm			
	Max. cutting length	8,00 mm			
	Helix	up			
	Max. RPM	50.000			
	<i>balanced* and polished</i>				
CE-RB153 	Shank diameter	6,00 mm	Zünd (1)	R108	3910738
	Total length	50,00 mm	Zünd (2)	R153	3910761
	Number of flutes	1	Kongsberg (1)	BIT-AUS06-3006-50	42445916
	Cutting edge diameter	3,00 mm	Kongsberg (2)	BIT-MUS06-3006-50	42443549
	Max. cutting length	6,00 mm	Summa	500-9854	
	Helix	up			
	Max. RPM	50.000			
	<i>balanced* and polished</i>				
CE-RB2064  <small>Zentrierzahn / Centering tooth</small>	Shank diameter	6,00 mm	Kongsberg (1)	BIT-MUS06-3006-50	42443549
	Total length	58,00 mm			
	Number of flutes	1			
	Cutting edge diameter	3,00 mm			
	Max. cutting length	6,00 mm			
	Helix	up			
	Max. RPM	50.000			
	<i>balanced* and polished</i>				
CE-RB208  <small>Zentrierzahn / Centering tooth</small>	Shank diameter	6,00 mm	Zünd (1)	R208	5212028
	Total length	58,00 mm			
	Number of flutes	1			
	Cutting edge diameter	3,00 mm			
	Max. cutting length	8,00 mm			
	Helix	up			
	Max. RPM	50.000			
	<i>balanced* and polished</i>				
CE-RB113 	Shank diameter	6,00 mm	Zünd (1)	R103	3910743
	Total length	50,00 mm	Zünd (2)	R113	3910763
	Number of flutes	1	Kongsberg (1)	BIT-MUS06-3011-50	42437905
	Cutting edge diameter	3,00 mm	Kongsberg (2)	BIT-AUS06-3011-50 (i-8005)	42437889
	Max. cutting length	11,00 mm	Summa	500-9876	
	Helix	up			
	Max. RPM	50.000			
	<i>balanced* and polished</i>				


Item	Technical data	Replacement for		
<i>* Balancing licensed from Datron AG</i>				
1.3. Up cut router bit, shank diameter 6,0 mm				
CE-RB203 	Shank diameter	6,00 mm	Zünd (1) R203	5209419
	Total length	58,00 mm	Zünd (2)	
	Number of flutes	1	Kongsberg (1)	
	Cutting edge diameter	3,00 mm	Kongsberg (2)	
	Max. cutting length	11,00 mm	Summa	
	Helix	up		
	Max. RPM	50.000		
	<i>balanced* and polished</i>			
CE-RB2069 	Shank diameter	6,00 mm	Kongsberg (1) BIT-MUS06-3014-50	42459537
	Total length	58,00 mm	Kongsberg (2) BIT-AUS06-3014-50	42458992
	Number of flutes	1		
	Cutting edge diameter	3,00 mm		
	Max. cutting length	14,00 mm		
	Helix	up		
	Max. RPM	50.000		
	<i>balanced* and polished</i>			
CE-RB109 	Shank diameter	6,00 mm	Zünd (1) R109	3910739
	Total length	50,00 mm	Kongsberg (1) BIT-MUS06-4006-50	42443564
	Number of flutes	1	Summa 500-9877	
	Cutting edge diameter	4,00 mm		
	Max. cutting length	6,00 mm		
	Helix	up		
	Max. RPM	50.000		
	<i>balanced* and polished</i>			
CE-RB154 	Shank diameter	6,00 mm	Zünd (1) R154	3910709
	Total length	50,00 mm	Kongsberg (1) BIT-AUS06-4008-50 (i-8011)	42445924
	Number of flutes	1		
	Cutting edge diameter	4,00 mm		
	Max. cutting length	8,00 mm		
	Helix	up		
	Max. RPM	50.000		
	<i>balanced* and polished</i>			
CE-RB209 	Shank diameter	6,00 mm	Zünd (1) R209	5212030
	Total length	58,00 mm		
	Number of flutes	1		
	Cutting edge diameter	4,00 mm		
	Max. cutting length	8,00 mm		
	Helix	up		
	Max. RPM	50.000		
	<i>balanced* and polished</i>			
CE-RB2011 	Shank diameter	6,00 mm		
	Total length	50,00 mm		
	Number of flutes	1		
	Cutting edge diameter	4,00 mm		
	Max. cutting length	10,00 mm		
	Helix	up		
	Max. RPM	50.000		
	<i>balanced* and polished</i>			
CE-RB114 	Shank diameter	6,00 mm	Zünd (1) R114	3910764
	Total length	50,00 mm	Kongsberg (1) BIT-MUS06-4012-50	42437863
	Number of flutes	1	Kongsberg (2) BIT-AUS06-4012-50	42437848
	Cutting edge diameter	4,00 mm	Summa 500-9856	
	Max. cutting length	12,00 mm		
	Helix	up		
	Max. RPM	50.000		
	<i>balanced* and polished</i>			



Item	Technical data	Replacement for			
<i>* Balancing licensed from Datron AG</i>					
1.3. Up cut router bit, shank diameter 6,0 mm					
CE-RB157 	Shank diameter	6,00 mm	Zünd (1)	R104	3910744
	Total length	50,00 mm	Zünd (2)	R157	3910795
	Number of flutes	1			
	Cutting edge diameter	4,00 mm			
	Max. cutting length	14,00 mm			
	Helix	up			
	Max. RPM	50.000			
<i>balanced* and polished</i>					
CE-RB204  <small>Zentrierzahn / Centering tooth</small>	Shank diameter	6,00 mm	Zünd (1)	R204	5209420
	Total length	58,00 mm			
	Number of flutes	1			
	Cutting edge diameter	4,00 mm			
	Max. cutting length	14,00 mm			
	Helix	up			
	Max. RPM	50.000			
<i>balanced* and polished</i>					
CE-RB170 	Shank diameter	6,00 mm	Zünd (1)	R158	3910796
	Total length	58,00 mm	Zünd (2)	R170	3910793
	Number of flutes	1	Kongsberg (1)	BIT-MUS06-4022-50	42443572
	Cutting edge diameter	4,00 mm	Kongsberg (2)	BIT-AUS06-4022-50	42442665
	Max. cutting length	22,00 mm			
	Helix	up			
	Max. RPM	50.000			
<i>balanced* and polished</i>					
CE-RB2012 	Shank diameter	6,00 mm			
	Total length	50,00 mm			
	Number of flutes	1			
	Cutting edge diameter	5,00 mm			
	Max. cutting length	6,00 mm			
	Helix	up			
	Max. RPM	50.000			
<i>balanced* and polished</i>					
CE-RB2067  <small>Zentrierzahn / Centering tooth</small>	Shank diameter	6,00 mm			
	Total length	58,00 mm			
	Number of flutes	1			
	Cutting edge diameter	5,00 mm			
	Max. cutting length	8,00 mm			
	Helix	up			
	Max. RPM	50.000			
<i>balanced* and polished</i>					
CE-RB2013 	Shank diameter	6,00 mm	Kongsberg (1)	BIT-MUS06-5012-50	42451062
	Total length	50,00 mm	Kongsberg (2)	BIT-AUS06-5012-50	42451047
	Number of flutes	1			
	Cutting edge diameter	5,00 mm			
	Max. cutting length	12,00 mm			
	Helix	up			
	Max. RPM	50.000			
<i>balanced* and polished</i>					
CE-RB173 	Shank diameter	6,00 mm	Zünd (1)	R115	3910758
	Total length	58,00 mm	Zünd (2)	R173	3910773
	Number of flutes	1			
	Cutting edge diameter	5,00 mm			
	Max. cutting length	16,00 mm			
	Helix	up			
	Max. RPM	50.000			
<i>balanced* and polished</i>					





Item	Technical data	Replacement for				
<i>* Balancing licensed from Datron AG</i>						
1.3. Up cut router bit, shank diameter 6,0 mm						
CE-RB205 	Shank diameter	6,00 mm	Zünd (1)	R205	5209421	
	Total length	58,00 mm				
	Number of flutes	1				
	Cutting edge diameter	5,00 mm				
	Max. cutting length	16,00 mm				
	Helix	up				
	Max. RPM	50.000				
	<i>balanced* and polished</i>					
	CE-RB171 	Shank diameter	6,00 mm	Zünd (1)	R159	3910797
		Total length	58,00 mm	Zünd (2)	R171	3910794
Number of flutes		1	Kongsberg (1)	BIT-MUS06-5022-58	42443598	
Cutting edge diameter		5,00 mm	Kongsberg (2)	BIT-AUS06-5022-58	42443762	
Max. cutting length		22,00 mm				
Helix		up				
Max. RPM		40.000				
<i>balanced* and polished</i>						
CE-RB1997 		Shank diameter	6,00 mm			
		Total length	50,00 mm			
	Number of flutes	1				
	Cutting edge diameter	6,00 mm				
	Max. cutting length	6,00 mm				
	Helix	up				
	Max. RPM	50.000				
<i>balanced* and polished</i>						
CE-RB2044 	Shank diameter	6,00 mm				
	Total length	58,00 mm				
	Number of flutes	1				
	Cutting edge diameter	6,00 mm				
	Max. cutting length	6,00 mm				
	Helix	up				
	Max. RPM	50.000				
<i>balanced* and polished</i>						
CE-RB2014 	Shank diameter	6,00 mm				
	Total length	50,00 mm				
	Number of flutes	1				
	Cutting edge diameter	6,00 mm				
	Max. cutting length	8,00 mm				
	Helix	up				
	Max. RPM	50.000				
<i>balanced* and polished</i>						
CE-RB2068 	Shank diameter	6,00 mm				
	Total length	58,00 mm				
	Number of flutes	1				
	Cutting edge diameter	6,00 mm				
	Max. cutting length	8,00 mm				
	Helix	up				
	Max. RPM	50.000				
<i>balanced* and polished</i>						
CE-RB101 	Shank diameter	6,00 mm	Zünd (1)	R101	3910740	
	Total length	50,00 mm	Kongsberg (1)	BIT-MUS06-6012-50	42451070	
	Number of flutes	1	Kongsberg (2)	BIT-AUS06-6012-50	42451054	
	Cutting edge diameter	6,00 mm	Summa	500-9857		
	Max. cutting length	12,00 mm				
	Helix	up				
	Max. RPM	50.000				
	<i>balanced* and polished</i>					

Item	Technical data		Replacement for		
<i>* Balancing licensed from Datron AG</i>					
1.3. Up cut router bit, shank diameter 6,0 mm					
CE-RB116 	Shank diameter	6,00 mm	Zünd (1)	R116	3910759
	Total length	58,00 mm	Kongsberg (1)	BIT-AUS06-6022-58	42442707
	Number of flutes	1	Summa	500-9858	
	Cutting edge diameter	6,00 mm			
	Max. cutting length	22,00 mm			
	Helix	up			
	Max. RPM	50.000			
<i>balanced* and polished</i>					
CE-RB100  <p style="font-size: small; color: red; margin-top: 5px;">Zentrierzahn / Centering tooth</p>	Shank diameter	6,00 mm	Zünd (1)	R100	3910741
	Total length	58,00 mm	Kongsberg (1)	BIT-MUS06-6022-58	42442715
	Number of flutes	1			
	Cutting edge diameter	6,00 mm			
	Max. cutting length	22,00 mm			
	Helix	up			
	Max. RPM	50.000			
<i>balanced* / non-polished</i>					
CE-RB206  <p style="font-size: small; color: red; margin-top: 5px;">Zentrierzahn / Centering tooth</p>	Shank diameter	6,00 mm	Zünd (1)	R206	5209422
	Total length	58,00 mm			
	Number of flutes	1			
	Cutting edge diameter	6,00 mm			
	Max. cutting length	22,00 mm			
	Helix	up			
	Max. RPM	50.000			
<i>balanced* and polished</i>					
CE-RB117 	Shank diameter	6,00 mm	Zünd (1)	R117	3910771
	Total length	58,00 mm			
	Number of flutes	1			
	Cutting edge diameter	6,00 mm			
	Max. cutting length	28,00 mm			
	Helix	up			
	Max. RPM	40.000			
<i>balanced* and polished</i>					
CE-RB156 	Shank diameter	6,00 mm	Zünd (1)	R156	3910710
	Total length	64,00 mm	Zünd (2)	R172	3910798
	Number of flutes	1	Kongsberg (1)	BIT-AUS06-6032-64	42438069
	Cutting edge diameter	6,00 mm			
	Max. cutting length	32,00 mm			
	Helix	up			
	Max. RPM	40.000			
<i>balanced* and polished</i>					
CE-RB118 (folgt)	Shank diameter	6,00 mm	Zünd (1)	R118	3910726
	Total length	75,00 mm			
	Number of flutes	2			
	Cutting edge diameter	6,00 mm			
	Max. cutting length	27,00 mm			
	Helix	up			
	Max. RPM	48.000			
<i>balanced* and polished</i>					

Item	Technical data	Replacement for				
<i>* Balancing licensed from Datron AG</i>						
1.4. Up cut router bit, shank diameter 8,0 mm						
	CE-RB5885	Shank diameter	8,00 mm	Vortex	5885	
	Total length	64,00 mm				
	Number of flutes	2				
	Cutting edge diameter	8,00 mm				
	Max. cutting length	25,00 mm				
	Helix	up				
	Max. RPM					
			<i>balanced* and polished</i>			
	CE-RB5585	Shank diameter	8,00 mm	Vortex	5585	
	Total length	64,00 mm				
	Number of flutes	2				
	Cutting edge diameter	8,00 mm				
	Max. cutting length	25,00 mm				
	Helix	up, straight				
	Max. RPM					
			<i>balanced* and polished</i>			
2.1. Down cut router bit, shank diameter 3,0 mm						
	CE-RB073	Shank diameter	3,00 mm	Zünd (1)	R73	3910754
	Total length	38,00 mm				
	Number of flutes	1				
	Cutting edge diameter	2,00 mm				
	Max. cutting length	6,00 mm				
	Helix	down				
	Max. RPM	65.000				
			<i>balanced* and polished</i>			
	CE-RB076	Shank diameter	3,00 mm	Zünd (1)	R76	3910757
	Total length	38,00 mm				
	Number of flutes	1				
	Cutting edge diameter	3,00 mm				
	Max. cutting length	11,00 mm				
	Helix	down				
	Max. RPM	65.000				
			<i>balanced* and polished</i>			

Item	Technical data	Replacement for			
<i>* Balancing licensed from Datron AG</i>					
2.2. Down cut router bit, shank diameter 6,0 mm					
CE-RB133 	Shank diameter	6,00 mm	Zünd (1)	R123	3910747
	Total length	58,00 mm	Zünd (2)	R133	3910767
	Number of flutes	1	Kongsberg (1)	BIT-MDS06-3011-50	42447342
	Cutting edge diameter	3,00 mm	Kongsberg (2)	BIT-ADS06-3011-50	42443358
	Max. cutting length	11,00 mm	Summa	500-9866	
	Helix	down			
	Max. RPM	50.000			
		<i>balanced* and polished</i>			
CE-RB124 	Shank diameter	6,00 mm	Zünd (1)	R124	3910748
	Total length	58,00 mm	Kongsberg (1)	BIT-MDS06-4012-50	42449389
	Number of flutes	1	Kongsberg (2)	BIT-ADS06-4012-50	42445957
	Cutting edge diameter	4,00 mm	Summa	500-9880	
	Max. cutting length	12,00 mm			
	Helix	down			
	Max. RPM	50.000			
		<i>balanced* and polished</i>			
CE-RB134 	Shank diameter	6,00 mm	Zünd (1)	R134	3910768
	Total length	58,00 mm			
	Number of flutes	1			
	Cutting edge diameter	4,00 mm			
	Max. cutting length	14,00 mm			
	Helix	down			
	Max. RPM	50.000			
		<i>balanced* and polished</i>			
CE-RB135 	Shank diameter	6,00 mm	Zünd (1)	R135	3910769
	Total length	58,00 mm			
	Number of flutes	1			
	Cutting edge diameter	5,00 mm			
	Max. cutting length	16,00 mm			
	Helix	down			
	Max. RPM	50.000			
		<i>balanced* and polished</i>			
CE-RB136 	Shank diameter	6,00 mm	Zünd (1)	R126	3910750
	Total length	58,00 mm	Zünd (2)	R136	3910770
	Number of flutes	1			
	Cutting edge diameter	6,00 mm			
	Max. cutting length	22,00 mm			
	Helix	down			
	Max. RPM	50.000			
		<i>balanced* and polished</i>			


Item	Technical data	Replacement for		
<i>* Balancing licensed from Datron AG</i>				
3.1. Compression router bit				
CE-RB2010 	Shank diameter	6,00 mm	Summa	500-9864
	Total length	65,00 mm		
	Number of flutes	2		
	Cutting edge diameter	6,00 mm		
	Max. cutting length	25,00 mm		
	Helix	compression		
	Max. RPM	60.000		
	<i>balanced* and polished</i>			
3.2. V-groove router bit				
CE-VG140 	Shank diameter	6,00 mm	Zünd (1)	R140
	Total length	46,00 mm	Kongsberg (1)	BIT-EBV06-94 (i-3772)
	Number of flutes	1		
	Cutting edge diameter	10,00 mm		
	Max. cutting length	4,10 mm		
	Helix	V-groove 90°		
	Max. RPM	25.000		
	<i>balanced* and polished</i>			
CE-VG141 	Shank diameter	6,00 mm	Zünd (1)	R141
	Total length	50,00 mm	Summa	500-9863
	Number of flutes	2		
	Cutting edge diameter	10,00 mm		
	Max. cutting length	4,00 mm		
	Helix	V-groove 90°		
	Max. RPM	40.000		
	<i>balanced* and polished</i>			


Item	Technical data	Replacement for			
<i>* Balancing licensed from Datron AG</i>					
Engraving router bit					
CE-EB003 	Shank diameter	3,00 mm	Zünd (1)	E3	3910503
	Total length	38,00 mm			
	Number of flutes	1			
	Cutting edge diameter	3,00 mm			
	Max. cutting length	3,90 mm			
	Helix	Engraving 36°			
	Max. RPM	50.000			
		<i>balanced* and polished</i>			
CE-EB006 	Shank diameter	6,00 mm	Zünd (1)	E6	3910506
	Total length	50,00 mm			
	Number of flutes	1			
	Cutting edge diameter	6,00 mm			
	Max. cutting length	2,70 mm			
	Helix	Engraving 92°			
	Max. RPM	50.000			
		<i>balanced* and polished</i>			
CE-EB007 	Shank diameter	6,00 mm	Zünd (1)	E7	3910507
	Total length	50,00 mm	Kongsberg (1)	BIT-EBV06-60	42444406
	Number of flutes	1			
	Cutting edge diameter	6,00 mm			
	Max. cutting length	4,70 mm			
	Helix	Engraving 60°			
	Max. RPM	50.000			
		<i>balanced* and polished</i>			
CE-EB008 	Shank diameter	6,00 mm	Zünd (1)	E8	3910508
	Total length	50,00 mm	Kongsberg (1)	BIT-EBV06-40	42444398
	Number of flutes	1			
	Cutting edge diameter	6,00 mm			
	Max. cutting length	7,50 mm			
	Helix	Engraving 40°			
	Max. RPM	50.000			
		<i>balanced* and polished</i>			

Item	Technical data	Replacement for
------	----------------	-----------------


** Balancing licensed from Datron AG*


3.4. micro-thoothed router bit






	CE-RR88002	Shank diameter	6,00 mm		
		Total length	50,00 mm		
		Number of flutes	micro-thoothed		
		Cutting edge diameter	4,00 mm		
		Max. cutting length	16,00 mm		
		Helix	Rasp router bit		
		Max. RPM			
			<i>balanced* and polished</i>		

	CE-RR88001	Shank diameter	6,00 mm		
		Total length	50,00 mm		
		Number of flutes	micro-thoothed		
		Cutting edge diameter	6,00 mm		
		Max. cutting length	16,00 mm		
		Helix	Rasp router bit		
		Max. RPM			
			<i>balanced* and polished</i>		

3.5. Diamond polish tool

	CE-PB106	Shank diameter	6,00 mm	Zünd (1)	P106	3910780
		Total length	50,00 mm	Kongsberg (1)	Diamond polish tool 5,8/6-6-50	42452169
		Number of flutes	1			
		Cutting edge diameter	6,00 mm			
		Max. cutting length	7,00 mm			
		Helix	up			
		Max. RPM	41.000			
			<i>Diamond polish tool</i>			

	CE-PB201	Shank diameter	6,00 mm	Zünd (1)	P201	5214210
		Total length	50,00 mm	Kongsberg (1)	Polycrystalline Diamond polish tool 14mm	42463646
		Number of flutes	1	Summa	500-9859	
		Cutting edge diameter	5,50 mm			
		Max. cutting length	16,00 mm			
		Helix	up			
		Max. RPM	50.000			
			<i>Diamond polish tool</i>			

Item	Technical data	Replacement for	
<i>* Balancing licensed from Datron AG</i>			
4.1. XOX coating for aluminum and aluminum composite panels			
CE-RB2065-XOX  Zentrierzahn / Centering tooth	Shank diameter	6,00 mm	Kongsberg (1) BIT-MUS06-2006-50C2
	Total length	58,00 mm	
	Number of flutes	1	
	Cutting edge diameter	2,00 mm	
	Max. cutting length	8,00 mm	
	Helix	up	
	Max. RPM	50.000	
<i>coated and balanced*</i>			
CE-RB208-XOX  Zentrierzahn / Centering tooth	Shank diameter	6,00 mm	Zünd (1) R208
	Total length	58,00 mm	Kongsberg (1) BIT-MUS06-3006-50C2
	Number of flutes	1	
	Cutting edge diameter	3,00 mm	
	Max. cutting length	8,00 mm	
	Helix	up	
	Max. RPM	50.000	
<i>coated and balanced*</i>			
CE-RB209-XOX  Zentrierzahn / Centering tooth	Shank diameter	6,00 mm	Zünd (1) R209
	Total length	58,00 mm	Kongsberg (1) BIT-MUS06-4006-50C2
	Number of flutes	1	
	Cutting edge diameter	4,00 mm	
	Max. cutting length	8,00 mm	
	Helix	up	
	Max. RPM	50.000	
<i>coated and balanced*</i>			
CE-RB2067-XOX  Zentrierzahn / Centering tooth	Shank diameter	6,00 mm	
	Total length	58,00 mm	
	Number of flutes	1	
	Cutting edge diameter	5,00 mm	
	Max. cutting length	8,00 mm	
	Helix	up	
	Max. RPM	50.000	
<i>coated and balanced*</i>			
CE-RB2068-XOX  Zentrierzahn / Centering tooth	Shank diameter	6,00 mm	
	Total length	58,00 mm	
	Number of flutes	1	
	Cutting edge diameter	6,00 mm	
	Max. cutting length	8,00 mm	
	Helix	up	
	Max. RPM	50.000	
<i>coated and balanced*</i>			

Item	Technical data	Replacement for				
<i>* Balancing licensed from Datron AG</i>						
4.2. DLC coating for plastics						
	CE-RB2064-DLC	Shank diameter	6,00 mm	Kongsberg (1)	BIT-MUS06-3006-50C1	42451104
	Total length	58,00 mm	Summa	500-9867		
	Number of flutes	1				
	Cutting edge diameter	3,00 mm				
	Max. cutting length	6,00 mm				
	Helix	up				
	Max. RPM	50.000				
		<i>coated and balanced*</i>				
	CE-RB2069-DLC	Shank diameter	6,00 mm	Kongsberg (1)	BIT-MUS06-3014-50 DLC coated	
	Total length	58,00 mm				
	Number of flutes	1				
	Cutting edge diameter	3,00 mm				
	Max. cutting length	14,00 mm				
	Helix	up				
	Max. RPM	50.000				
		<i>coated and balanced*</i>				
	CE-RB2070-DLC	Shank diameter	6,00 mm	Zünd (1)	R104 DLC coated	
	Total length	58,00 mm	Zünd (2)	R157 DLC coated		
	Number of flutes	1	Summa	500-9868		
	Cutting edge diameter	4,00 mm				
	Max. cutting length	14,00 mm				
	Helix	up				
	Max. RPM	50.000				
		<i>coated and balanced*</i>				
	CE-RB2071-DLC	Shank diameter	6,00 mm			
	Total length	58,00 mm				
	Number of flutes	1				
	Cutting edge diameter	5,00 mm				
	Max. cutting length	18,00 mm				
	Helix	up				
	Max. RPM	50.000				
		<i>coated and balanced*</i>				
	CE-RB117-DLC	Shank diameter	6,00 mm	Zünd (1)	R117 DLC coated	
	Total length	58,00 mm				
	Number of flutes	1				
	Cutting edge diameter	6,00 mm				
	Max. cutting length	28,00 mm				
	Helix	up				
	Max. RPM	40.000				
		<i>coated and balanced*</i>				